P25922

# ELECTROMAGNETIC TRANSDUCER
# AND
# PORTABLE COMMUNICATION DEVICE

# BACKGROUND OF THE INVENTION

## 1. FIELD OF THE INVENTION:

The present invention relates to an electroacoustic transducer of an electromagnetic type for use in a portable communication device, e.g., a cellular phone or a pager, for reproducing an alarm sound or melody sound responsive to a received call and for reproducing voices and the like, and a portable communication device including the electroacoustic transducer of an electromagnetic type.

## 2. DESCRIPTION OF THE RELATED ART:

Figures **9A** and **9B** are plan and cross-sectional views showing a conventional electroacoustic transducer **2000** of an electromagnetic type (hereinafter referred to as an electromagnetic transducer).

The conventional electromagnetic transducer **2000** includes a cylindrical housing **107** and a disk-shaped yoke **106** disposed so as to cover the bottom face of the housing **107**. A center pole **103**, which forms an integral part of the yoke **106**, is provided in a central portion of the yoke **106**. A coil **104** is wound around the center pole **103**. Spaced from the outer periphery of the coil **104** is provided an annular magnet **105**, with an appropriate interspace maintained between the coil **104** and the inner periphery of the annular magnet **105** around the entire periphery of the coil **104**. The outer peripheral surface of the magnet **105** is abutted to the inner peripheral surface of the housing **107**. An upper end of the housing **107** supports a disk-shaped diaphragm **100** so that an appropriate interspace exists between the first diaphragm **100** and the magnet **105**, the coil **104**, and the center pole **103**. A

magnetic member **101** is provided on the diaphragm **100** so as to be concentric with the diaphragm **100**.

Now, an operation of the above-described conventional electromagnetic transducer **2000** will be described.

In an initial state where no current flows through the coil **104**, a magnetic path is formed by the magnet **105**, the magnetic member **101**, the center pole **103**, and the yoke **106**. As a result, the magnetic member **101** is attracted toward the magnet **105** and the center pole **103**, up to a point of equilibrium with the elastic force of the diaphragm **100**. If an alternating current flows through the coil **104** in this initial state, an alternating magnetic field is generated in the aforementioned magnetic path, so that a driving force is generated on the magnetic member **101**. Such a driving force generated on the magnetic member **101** causes the magnetic member **101** to be displaced from its initial state, along with the fixed diaphragm **100**, due to an interaction with an attraction force which is generated by the magnet **105** and the driving force. The vibration caused by such displacement transmits sound.

The lower limit of a frequency band to be reproduced by an electromagnetic transducer is generally dependent on the minimum resonance frequency of a vibrating system. A vibrating system as used herein refers to a group of elements included in an electromagnetic transducer which actually vibrate so as to produce sound. In the conventional electromagnetic transducer **2000**, the minimum resonance frequency cannot be reduced to such a level that a low frequency signal, such as an audio signal, can be reproduced.

The reason will be described below.

The minimum resonance frequency of the electromagnetic transducer **2000** is dependent on the stiffness of a vibrating system, which is obtained as a difference between an elastic force of the diaphragm **100** and an attraction force generated on the magnetic member **101** by the magnet **105**.

Figure **10** shows a relationship between the force-displacement characteristics curve of the diaphragm **100** and the attraction force generated on the magnetic member**101** by the magnet**105**. In Figure **10**, the vertical axis represents a force while the horizontal axis represents a displacement of the diaphragm **100**. An intersection **A** between a curve indicating the force-displacement characteristics of the diaphragm **100** and a curve indicating the attraction force generated on the magnetic member**101** by the magnet**105** represents a point where the elastic force of the diaphragm **100** is balanced with the attraction force. The minimum resonance frequency is dependent on a difference between the elastic force of the diaphragm **100** and the attraction force where the intersection **A** is regarded as an original point.

It is necessary to decrease the elastic constant of the diaphragm **100** in order to reduce the minimum resonance frequency. However, when the elastic constant of the diaphragm **100** is excessively small (i.e., no intersection **A** exists), the magnetic member **101** is trapped by the center pole **103** along with the diaphragm **100**. Therefore, since the elastic constant must be the range in which the intersection **A** exists, the possible minimum resonance

frequency is limited. Due to such a constraint, the minimum resonance frequency of the conventional electromagnetic transducer **2000** is typically about 2.5 kHz or more. Therefore, a low frequency signal, such as an audio signal, cannot be reproduced by the conventional electromagnetic transducer **2000**.

## SUMMARY OF THE INVENTION

According to one aspect of the present invention, an electromagnetic transducer includes a magnetic member, a suspension for supporting the magnetic member at a central portion of the suspension, a diaphragm connected to the suspension, a magnet for generating magnetic flux on the magnetic member, and a coil for generating alternating magnetic flux on the magnetic member.

In one embodiment of this invention, the stiffness of the suspension is greater than the stiffness of the diaphragm with respect to a vibration direction.

In one embodiment of this invention, the electromagnetic transducer further includes a center pole provided at an inner periphery side of the coil, and a yoke provided at a side of the coil opposite to the diaphragm. The magnet surrounds the coil.

In one embodiment of this invention, the diaphragm comprises a resin.

In one embodiment of this invention, the suspension comprises a metal.

In one embodiment of this invention, the suspension comprises a non-magnetic material.

In one embodiment of this invention, the electromagnetic transducer further includes a thin magnetic plate provided between the magnet and the diaphragm.

In one embodiment of this invention, an opening is provided at a central portion of the magnetic member.

In one embodiment of this invention, the electromagnetic transducer further includes a cover for covering the opening.

According to another aspect of the present invention, an electromagnetic transducer includes a magnetic member, a suspension for supporting the magnetic member at a central portion of the suspension, a diaphragm connected to the suspension, a yoke opposed to the diaphragm, a center pole provided at a diaphragm side of the yoke, a coil surrounding the center pole, and a magnet surrounding the coil. An opening is provided in each of the magnetic member and the suspension, the center pole is shaped so as to be inserted into the openings, and an upper face of the center pole is positioned higher than or equal to a bottom face of the magnet member.

In one embodiment of this invention, the suspension and the magnetic member are integrated together.

In one embodiment of this invention, an outer periphery of the diaphragm and an outer periphery of the suspension are positioned on the same plane.

According to another aspect of the present invention, a portable communication device includes the above-described electromagnetic transducer.

Thus, the invention described herein makes possible the advantages of providing (1) an electromagnetic transducer having a satisfactory acoustic characteristic capable of reproducing a low frequency signal, such as an audio signal; and (2) a portable communication terminal including the transducer.

These and other advantages of the present invention will become apparent to those skilled in the art upon reading and understanding the following detailed description with reference to the accompanying figures.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure **1** is a diagram showing an electromagnetic transducer according to Example 1 of the present invention.

Figure **2** is a diagram showing a magnetic member in the electromagnetic transducer of Example 1.

Figure **3** is a diagram showing a suspension in the electromagnetic transducer of Example 1.

Figure **4** is a diagram showing an electromagnetic transducer according to Example 2 of the present invention.

Figures **5A** to **5C** are diagrams showing a magnetic member, a suspension and a diaphragm in the electromagnetic

transducer of Example 2, respectively.

Figure **6** is a diagram showing an electromagnetic transducer according to Example 3 of the present invention.

Figure **7** is a diagram showing a suspension in the electromagnetic transducer of Example 3.

Figure **8A** is a diagram showing a portable communication terminal according to Example 4 of the present invention.

Figure **8B** is a block diagram showing an internal configuration of the portable communication terminal of Figure **8A**.

Figures **9A** and **9B** are diagrams showing a conventional electromagnetic transducer.

Figure **10** is a diagram showing a force-displacement characteristics curve of a diaphragm, and an attraction force generated on a magnetic member by a magnet, in the conventional electromagnetic transducer of Figures **9A** and **9B**.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Hereinafter, the present invention will be described by way of illustrative examples with reference to the accompanying drawings.

(Example 1)

An electromagnetic transducer **1000** according to

Example 1 of the present invention will be described with reference to Figures **1**, **2** and **3**.

Figure **1** is a cross-sectional view showing the electromagnetic transducer **1000**. The electromagnetic transducer **1000** includes a disk-shaped yoke **6**, a cylindrical housing **7** surrounding the disk-shaped yoke **6**, a center pole **3** provided in a central portion of the yoke **6**, a coil **4** wound around the center pole **3**, an annular magnet **5** spaced from the outer periphery of the coil **4**, a suspension **1** supported by the housing **7** in such a manner as to be able to vibrate, a magnetic member **2** provided in a central portion of the suspension **1**, a cylindrical spacer **10** provided on the housing **7**, and a diaphragm **9** supported by the spacer **10** in such a manner as to be able to vibrate.

The central portion of the diaphragm **9** is connected with the suspension **1**. An appropriate interspace is maintained between the coil **4** and the inner periphery of the annular magnet **5** around the entire circumference thereof. Further, an appropriate interspace is maintained between the outer periphery of the magnet **5** and the inner periphery of the housing **7** around the entire circumference thereof. An appropriate interspace is maintained between the suspension **1**, and the coil **4**, the center pole **3** and the magnet **5**. A plurality of air holes **8** for releasing out air between the diaphragm **9** and the yoke **6** are provided on the bottom face of the housing **7** so as to reduce an acoustic load on the diaphragm **9**.

Figure **2** is a plan view of the electromagnetic transducer **1000**, showing that the magnetic member **2** is in the shape of a disk. Figure **3** is a plan view of the

suspension 1 of the electromagnetic transducer **1000**. As shown in Figures **1** and **3**, the suspension **1** includes a central portion **31** at which a magnetic member **2** is provided, an outer periphery portion **32** supported by the housing **7**, and a plurality of radial portions **33** connecting between the central portion **31** and the outer periphery portion **32**. As shown in Figure **1**, the diaphragm **9** is in the shape of a cone having a downroll-shaped periphery. The stiffness in a vibration direction **30** of the suspension **1** is greater than the stiffness in the vibration direction **30** of the diaphragm **9**.

In Example 1, materials for the suspension **1**, the magnetic member **2**, and the diaphragm **9** are stainless steel, permalloy, and PEN (Poly Ethylene Naphthalate), respectively.

An operation of the aforementioned electromagnetic transducer **1000** will be described below.

In an initial state where no current flows through the coil **4**, a magnetic path is formed by the magnet **5**, the magnetic member **2**, the center pole **3**, and the yoke **6**. Due to this magnetic path, a downward attraction force is exerted on the magnetic member **2**, so that the suspension **1** is displaced downward along with the magnetic member **2**. In addition, the diaphragm **9** connected to the suspension **1** is displaced downward. In this case, when an alternating current flows through the coil **4** and an alternating magnetic field is therefore generated, a driving force is generated on the magnetic member **2**. This driving force causes the magnetic member **2** as well as the suspension **1** and the diaphragm **9** to be displaced from the initial state. The

vibration caused by such displacement of the diaphragm **9** transmits sound.

In the electromagnetic transducer **1000**, the stiffness in the vibration direction **30** of the suspension **1** is greater than the stiffness in the vibration direction **30** of the diaphragm **9**. For example, the electromagnetic transducer **1000** is designed so that the stiffness in the vibration direction **30** of the suspension **1** is seven times greater than the stiffness in the vibration direction **30** of the diaphragm **9**. Since the stiffness of the suspension **1** is greater, the magnetic member **2** on which the attraction force is always exerted is substantially supported by the suspension **1**. As is different from the conventional electromagnetic transducer **2000**, the diaphragm **9** does not need to support the magnetic member **2**.

Therefore, the shape of the diaphragm **9** can be designed without taking into consideration the support of the magnetic member **2** by the diaphragm **9**. As a result, the stiffness of the diaphragm **9** is substantially not great when the diaphragm **9** is largely vibrated, as compared to conventional diaphragms. Therefore, the minimum resonance frequency can be reduced (e.g., 700 to 800 Hz), thereby making it possible to reproduce a low frequency signal, such as an audio signal.

Further, when the diameter of the diaphragm **9** is, for example, **15** mm, the effective radius of the diaphragm **9** within which the diaphragm **9** is actually vibrated can be increased by 10% or more as compared to when the diaphragm **9** is designed while taking into consideration the support of the magnetic member **2** by the diaphragm **9**. Therefore, a

sound pressure in reproduction can be improved.

In the electromagnetic transducer **1000**, the suspension **1** does not need to play a role in making a sound, so the suspension **1** is designed only with the support of the magnetic member **2** taken into consideration. Therefore, the suspension **1** can be realized using a flat plate as shown in Figure **3**, so that components can be more precisely fabricated as compared to when a diaphragm is formed so as to support a magnetic member as in conventional electromagnetic transducers, resulting in a reduction in variation in the performance of a product. Since the elastic force of the suspension **1** is designed to be greater than the attraction force, the magnetic member **2** is not trapped by the center pole **3** even when the elastic force of the diaphragm **9** is small.

A metal material for the suspension **1**, such as stainless steel, substantially does not change over time due to the attraction force which is always exerted on the magnetic member **2**. When a metal material, such as stainless steel, is used for the suspension **1** which substantially supports the magnetic member **2**, an electromagnetic transducer having a durability which substantially does not change over time can be achieved.

Further, when the suspension **1** is made of a non-magnetic or weak-magnetic material, the suspension **1** is substantially not influenced by the attraction force of the magnet **5**. Therefore, in this case, the shape of the suspension **1** can be more easily designed.

Since the diaphragm **9** does not need to support the

magnetic member **2**, the design of the shape of the diaphragm **9** for a desired acoustic characteristic is easy. As described above, it is possible to reduce a change in the stiffness of the diaphragm **9** depending on the amplitude, so that a low frequency signal, such as an audio signal, can be reproduced. In addition, distortion of the diaphragm **9** can be reduced. Further, the flatness of an amplitude characteristic of the diaphragm **9** with respect to an input voltage can be improved. Thus, the diaphragm **9** can be freely designed so as to obtain a satisfactory acoustic characteristic. A resin material, such as PEN, is easy to process and shape. Therefore, when the diaphragm **9** is made of a resin material, such as PEN, it is easy to design the diaphragm **9** to have a satisfactory acoustic characteristic.

In Example 1, the suspension **1** is made of stainless steel and the diaphragm **9** is made of PEN. The present invention is not limited to this. For example, if heat resistance is taken into consideration, the suspension **1** and the diaphragm **9** may be made of a metal material for both, or a metal material and a heat-resistance resin material, respectively. Alternatively, although the suspension **1** is made of a non-magnetic material, a magnetic material may be used to enhance the driving force. Further, the suspension **1** may be made of permalloy, which is the same material as that of the magnetic member **2**, in terms of an interface therebetween.

In Example 1, the suspension **1** has three arms extending in a radial direction. The suspension **1** may be in the shape of a butterfly or other shapes. Further, although the diaphragm **9** is in the shape of a cone, the diaphragm **9** may be in the shape of a dome or other shapes.

(Example 2)

An electromagnetic transducer **1100** according to Example 2 of the present invention will be described with reference to Figures **4** and **5**.

Figure **4** is a cross-sectional view showing the electromagnetic transducer **1100**. The electromagnetic transducer **1100** includes a coil **4**, a yoke **6**, a housing **7**, an air hole **8** and a spacer **10** which are the same as those of the electromagnetic transducer **1000** of Figure **1**.

Figures **5A**, **5B** and **5C** are plan views of elements of the electromagnetic transducer **1100**. As shown in these figures, the electromagnetic transducer **1100** further includes a annular magnetic member **12** having an opening provided in a central portion thereof, a suspension **11**, a diaphragm **19**, a center pole **13** having a shape which enables the center pole **13** to be inserted into the opening, a cover **20** covering the opening, a magnet **25** having a hollow portion, and a thin magnetic plate **15** provided in the hollow portion of the magnet **25**. The upper face of the center pole **13** is positioned higher than or equal to the bottom face of the magnetic member **12**.

The diaphragm **19** is made of a resin material, PEN, which is a non-magnetic material, as in Example 1, and the suspension **11** is made of permalloy which is a magnetic material.

An operation of the aforementioned electromagnetic transducer **1100** will be described below.

In an initial state where no current flows through the coil **4**, a magnetic path is formed by the magnet **25**, the thin magnetic plate **15**, the magnetic member **12**, the center pole **13** and the yoke **6**. As a result, an attraction force is generated on the magnetic member**12**. If an alternating current flows through the coil **4**, a driving force is generated on the magnetic member **12** in addition to the attraction force, so that the diaphragm **19** is vibrated.

In Example 2, the thin magnetic plate **15** is provided on the magnet **25**. Therefore, magnetic flux in the magnetic path can be efficiently transmitted into the magnetic member **12**, so that the magnetic resistance of the entire magnetic path can be reduced. Therefore, the magnetic flux density in the magnetic member **12** is large, so that the driving force generated on the magnetic member **12** is also large, thereby making it possible to improve a sound pressure.

Further, in Example 2, the center pole **13** is positioned substantially as high as the magnetic member **12**. Therefore, the magnetic member **12** is vibrated while the center pole **13** is passed through the center of the magnetic member **12**. Since the center pole **13** and the magnetic member **12** are located on substantially the same plane, a magnetic gap between the magnetic member **12** and the center pole **13** is maintained to be narrow as compared to conventional apparatuses even when a gap between the magnet **25** and the magnetic member **12** is increased as the amplitude of vibration is increased. Therefore, the magnetic resistance of the entire magnetic path is small. Therefore, the driving force can be improved as compared to the conventional electromagnetic transducer **1100** of

Figure **9**. As a result, it is possible to secure a driving force for a sufficient sound pressure, even when a gap between the magnet **25** and the magnetic member **12** is large so that the amplitude range can be increased. With the annular magnetic member **12**, suspension **11** and diaphragm **19**, the weight of the vibrating system can be light, so that a sound pressure can be increased.

In Example 2, the opening passing through the magnetic member **12**, the suspension **11** and the diaphragm **19** is covered with the cover **20** so as to substantially completely block emission of sound from a gap between the center pole **13** and the magnetic member **12**. However, when the emission of sound from the gap can be substantially blocked due to a relationship between the gap and the air hole **8**, the cover **20** may not be required. Although in Example 2 the cover **20** is an independent part, the cover **20** may be integrated with the diaphragm **19**.

In Example 2, the thin magnetic plate **15** is provided on the magnet **25**. However, when a sufficient driving force is obtained only by a magnet, or when there is not sufficient space for the thin magnetic plate **15**, the thin magnetic plate **15** may not be provided.

Although in Example 2 the diameter of the center pole **13** is constant as shown in Figure **4**, the diameter of the center pole **13** may be changed in a height direction. For example, when the diameter is decreased toward the yoke **6**, the magnetic gap between the magnetic member **12** and the center pole **13** is increased as the magnetic member **12** is displaced downward. Therefore, a reduction in the driving force due to magnetic saturation of the magnetic member **12**

can be suppressed.

(Example 3)

An electromagnetic transducer **1200** according to Example 3 of the present invention will be described with reference to Figures **6** and **7**.

Figure **6** is a cross-sectional view of the electromagnetic transducer **1200**. A coil **4**, a yoke **6**, an air hole **8**, a center pole **13**, a thin magnetic plate **15** and a magnet **25** of the electromagnetic transducer **1200** are the same as those of the electromagnetic transducer **1100** of Example 2 in Figure **4**.

Figure **7** is a plan view of a suspension **21** of the electromagnetic transducer **1200**. Referring to Figures **6** and **7**, the electromagnetic transducer **1200** further includes the suspension **21** into which a magnetic member **12'** is integrated, a cylindrical housing **27** supporting the suspension **21** by its periphery, and a diaphragm **29** which is an integral part of the cover **20'**. The outer periphery of the diaphragm **29** is substantially identical to that of the suspension **21**, so that the outer periphery of the diaphragm **29** matches that of the suspension **21** on the same plane.

The diaphragm **29** is made of a resin material, PEN, as in Example 1 while the suspension **21** into which the magnetic member **12'** is integrated is made of permalloy.

An operation of the aforementioned electromagnetic transducer **1200** will be described below.

In an initial state where no current flows through the coil **4**, a magnetic path is formed by the magnet **25**, the thin magnetic plate **15**, the suspension **21**, the center pole **13**, and the yoke **6** as in Example 2. A vibrating operation of the electromagnetic transducer **1200** is the same as in Example 2.

The electromagnetic transducer **1200** of Example 3 differs from the electromagnetic transducer **1100** of Example 2 in that the magnetic member **12'** is integrated with the suspension **21**, and the diaphragm **29** is integrated with the cover **20'**, so that such integration allows for a decrease in the numbers of elements and fabrication steps and therefore manufacturing cost can be reduced. Such integration also leads to a reduction in variations in assembly and therefore variations in characteristics of a product can be minimized. Further, as shown in Figure **7**, the suspension **21** and the magnetic member **12'** may be integrated into the same flat plate.

In the electromagnetic transducer **1200**, the outer periphery of the diaphragm **29** is substantially identical to that of the suspension **21**, so that the outer periphery of the diaphragm **29** matches that of the suspension **21** on the same plane. Therefore, it is easy to align the suspension **21** and the diaphragm **29**, so that variations in assembly are reduced and therefore variations in characteristics of a product can be minimized.

(Example 4)

As Example 4 of the present invention, a cellular phone **61** will be described with reference to Figures **8A** and **8B**, which is a portable communication device incorporating

the electromagnetic transducer according to the present invention.

Figure **8A** is a partially-cutaway perspective view of the cellular phone **61** according to Example 4 of the present invention. Figure **8B** is a block diagram schematically illustrating the structure of the cellular phone **61**.

The cellular phone **61** includes a housing **62**, which has a sound hole **63**, and an electromagnetic transducer **64**. As the electromagnetic transducer **64** to be incorporated in the cellular phone **61**, any one of the electromagnetic transducers **1000**, **1100** and **1200** illustrated in Examples 1, 2 and 3 can be employed. The electromagnetic transducer **64** is disposed in such an orientation that its diaphragm opposes the sound hole **63**.

As shown in Figure **8B**, the cellular phone **61** further includes an antenna **150**, a transmission/reception circuit **160**, a call signal generation circuit **161**, and a microphone **152**. The transmission/reception circuit **160** includes a demodulation section **160a**, a modulation section **160b**, a signal switching section **160c**, and a message recording section **160d**.

The antenna **150** is used in order to receive radiowaves which are output from a nearby base station and to transmit radiowaves to the base station. The demodulation section **160a** demodulates and converts a modulated signal which has been input via the antenna **150** into a received signal, and outputs the received signal to the signal switching section **160c**. The signal switching

section **160c** is a circuit which switches between different signal processes depending on the contents of the received signal. If the received signal is a signal indicative of a received call (hereinafter referred to as a "call received" signal), the received signal is output to the call signal generation circuit **161**. If the received signal is a voice signal, it is output to the electromagnetic transducer **64**. If the received signal is a voice signal for message recording, the received signal is output to the message recording section **160d**. The message recording section **160d** is composed of a semiconductor memory (not shown), for example. Any recorded message which is left while the cellular phone **61** is ON is stored in the message recording section **160d**. Any recorded message which is left while the cellular phone **61** is out of serviced areas or while the cellular phone **61** is OFF is stored in a memory device within the base station. The call signal generation circuit **161** generates a call signal, which is output to the electromagnetic transducer **64**.

As is the case with conventional cellular phones, the cellular phone **61** includes a small microphone **152** as an electromagnetic transducer. The modulation section **160b** modulates a dial signal and/or a voice signal which has been transduced by the microphone **152** and outputs the modulated signal to the antenna **150**.

Now, an operation of the cellular phone **61** as a portable communication device having the above structure will be described.

The radiowaves which are output from the base station are received by the antenna **150**, and are demodulated

by the demodulation section **160a** into a base-band received signal. Upon determination that the received signal is a call received signal, the signal switching circuit **160c** outputs a signal indicative of a received call to the call signal generation circuit **161** in order to inform the user of the cellular phone **61** of the received call.

Upon receiving a call received signal, the call signal generation circuit **161** outputs a call signal. The call signal includes a signal corresponding to a pure tone in the audible range or a complex sound composed of such pure tones. When the signal is input to the electromagnetic transducer **64**, the electromagnetic transducer **64** outputs a ringing tone to the user.

Once the user enters a talk mode, the signal switching circuit **160c** performs a level adjustment of the received signal, and thereafter outputs the received voice signal directly to the electromagnetic transducer **64**. The electromagnetic transducer **64** operates as a receiver or a loudspeaker to reproduce the voice signal.

The voice of the user is detected by the microphone **152** and converted into a voice signal, which is input to the modulation section **160b**. The voice signal is modulated by the modulation section **160b** onto a predetermined carrier wave, which is output via the antenna **150**.

If the user has set the cellular phone **61** in a message recording mode and leaves the cellular phone **61** ON, any recorded message that is left by a caller will be stored in the message recording section **160d**. If the user has

turned the cellular phone **61** OFF, any recorded message that is left by a caller will be temporarily stored in the base station. As the user requests reproduction of the recorded message via a key operation, the signal switching circuit **160c** receives such a request, and retrieves the recorded message from the message recording section **160d** or from the base station. The voice signal is adjusted to an amplified level and output to the electromagnetic transducer **64**. Then, the electromagnetic transducer **64** operates as a receiver or a loudspeaker to reproduce the recorded message.

Many electromagnetic transducers incorporated in portable communication devices, such as conventional cellular phones, have a high minimum resonance frequency, and are therefore only used for reproducing a ringing tone.

However, the electromagnetic transducer according to the present invention can have a low minimum resonance frequency. When incorporated in a portable communication device, the electromagnetic transducer according to the present invention can also be used for reproducing a voice signal, so that both a ringing tone and a voice signal can be reproduced by the same electromagnetic transducer. Thus, the number of acoustic elements to be incorporated in the portable communication device can be effectively reduced.

In the illustrated cellular phone **61**, the electromagnetic transducer **64** is mounted directly on the housing **62**. However, the electromagnetic transducer **64** may be mounted on a circuit board which is internalized in the cellular phone **61**. An acoustic port for increasing the sound pressure level of the ringing tone may be additionally

included.

Further, although in the electromagnetic transducer **64**, the diaphragm is opposed to the sound hole, the yoke may be opposed to the sound hole.

Although a cellular phone is illustrated in Figures **8A** and **8B** as a portable communication device, the present invention is applicable to any portable communication device that incorporates an electromagnetic transducer, such as a pager, a notebook-type personal computer, a PDA or a watch.

The electromagnetic transducer of the present invention includes a magnetic member, a suspension supporting and fixing the magnetic member at its central portion, and a diaphragm connected to the suspension. As is different from conventional electromagnetic transducers, the magnetic member is supported by the suspension, the diaphragm does not need to support the magnetic member. Therefore, the shape of the diaphragm can be freely designed so as to obtain a satisfactory acoustic characteristic. Further, the elastic constant of the diaphragm can be reduced so that a low frequency signal, such as an audio signal, can be reproduced. In addition, distortion of the diaphragm can be reduced, and the flatness of the sound pressure-frequency characteristics of the diaphragm can be improved.

Further, according to the electromagnetic transducer of the present invention, the suspension supporting the magnetic member is made of metal material, such as stainless steel. Therefore, an electromagnetic transducer having a durability which substantially does not

change over time can be realized. Since the suspension supports the magnetic member, an electromagnetic transducer capable of obtaining a satisfactory acoustic characteristic and reliability can be provided.

Further, according to the electromagnetic transducer of the present invention, the thin magnetic plate is provided between the magnet and the diaphragm, so that magnetic flux can be efficiently transmitted into the magnetic member, resulting in a large driving force. Therefore, sound pressure can be large.

Furthermore, according to the electromagnetic transducer, the magnetic member and the suspension each have an opening at a central portion thereof, and the center pole is passed through the openings, so that it is possible to reduce a gap between the magnetic member and the center pole forming a magnetic path. As a result, a driving force sufficient to largely vibrate the diaphragm can be obtained, thereby making it possible to reproduce a high sound pressure.

The portable communication device of the present invention includes the electromagnetic transducer of the present invention. Therefore, a single electromagnetic transducer can reproduce an alarm sound or melody sound, and voice. As a result, the number of acoustic transducers, a plurality of which are generally included in conventional portable communication terminals, can be reduced.

Various other modifications will be apparent to and can be readily made by those skilled in the art without departing from the scope and spirit of this invention.

Accordingly, it is not intended that the scope of the claims appended hereto be limited to the description as set forth herein, but rather that the claims be broadly construed.